



Department of Administrative Services

Purchasing and Contracts

500 S Grand Central Pky 4th Fl • Box 551217 • Las Vegas NV 89155-1217
(702) 455-2897 • Fax (702) 386-4914

Sabra Smith Newby, Chief Administrative Officer
Adleen B. Stidhum, Purchasing Manager



CLARK COUNTY, NEVADA BID NO. 603228-14 ANNUAL REQUIREMENTS MAINTENANCE CONTRACT FOR CARPET AND VINYL FLOORING

March 18, 2015

ADDENDUM NO. 2

INVITATION TO BID

1. The Bid opening date of March 30, 2015 at 3:00:00 p.m. **remains unchanged.**

TECHNICAL SPECIFICATIONS

2. **Delete** Section IV –Technical Specification pages IV-1 through IV-6 and **replace** with Section IV – Technical Specification Revised per Addendum No.2 pages IV-1 through IV-6 attached hereto (revisions are identified in bold print).

Except as modified herein all other bid specifications, terms, and special provision shall remain the same. Should you have any questions, I can be reached via email at Chetanc@ClarkCountyNV.Gov.

ISSUED BY:

A handwritten signature in black ink, appearing to read "Chetan Champneri".

CHETAN CHAMPANERI
Purchasing Analyst

Cc: Chuck James, Real Property Management
Darren R. Daniels, Real Property Management
Brian Connolly, Real Property Management
John Rodriguez, Real Property Management
Fernando Martinez, Real Property Management
Wayne Wedlow, Real Property Management

IV – TECHNICAL SPECIFICATIONS

BID NO. 603228-14

ANNUAL REQUIREMENTS MAINTENANCE CONTRACT FOR CARPET AND VINYL FLOORING REVISED PER ADDENDUM NO. 2

Name of Firm

INTENT:

It is the intent of these specifications to provide carpet and flooring materials that will conform to the specifications, and be suitable for continuous use by the COUNTY. The carpet and flooring offered shall be new, unused, the current production model and conform to the specifications provided below.

The carpet and flooring shall comply with all Federal and State of Nevada Emission Control Regulations, and Safety Standards in effect at the time of delivery to the COUNTY.

These specifications shall be construed as minimum requirements. Should the manufacturer's current published data or specifications exceed these, they shall be considered as minimum and be furnished by the Bidder.

BIDDERS MUST RETURN THE ORIGINAL OR A PHOTOCOPY OF THIS FORM AND MAKE AN ENTRY FOR EACH SPECIFICATION IN THE SPACE PROVIDED OPPOSITE THE SPECIFICATIONS, INDICATING ANY VARIANCES IN THE SPECIFICATION. IF THERE IS NOT ENOUGH SPACE, ATTACH AN ADDITIONAL SHEET OF PAPER.

<u>SPECIFICATION NO. 1</u>			
HIGH PERFORMANCE/TRAFFIC CARPET			
A.	CARPET CONSTRUCTION/ SURFACE TEXTURE:	TUFTED/ LOOP PILE	__ YES __ NO
B	CARPET SIZE:	6FT OR 12FT WIDE	__ YES __ NO
C	YARN WEIGHT (PER SQ. YD.):	GREATER THAN OR EQUAL TO 24oz	__ YES __ NO
D	FACE YARN:	TYPE 6, 6 and/or Type 6	__ YES __ NO
E	DYE SYSTEM:	YARN OR SOLUTION DYED	__ YES __ NO
F	PRIMARY BACKING MATERIAL:	WOVEN SYNTHETIC. JUKE/CANVAS BACK WILL NOT BE ACCEPTED.	__ YES __ NO
G	PRIMARY/SECONDARY BACKING:	IMPERMEABLE MOISTURE BARRIER	__ YES __ NO
H	TUFT BIND TEST (ASTM D-1335):	LOOP PILE – 3.0 LBS. MINIMUM AVERAGE VALUE	__ YES __ NO
I	CROCKING TEST (AATCC 165)	COLOR TRANSFER CLASS 4 MINIMUM, WET AND DRY, WHEN TESTED AS SPECIFIED	__ YES __ NO
J	COLORFASTNESS TO LIGHT TEST (AATCC 16, OPT 3):	COLOR CHANGE BETWEEN THE EXPOSED AND UNEXPOSED CARPET AREAS EQUIVALENT TO A MINIMUM OF GRADE 4 ON THE GRAY SCALE FOR COLOR CHANGE AFTER AN EXPOSURE OF 40 AFU (AATCC FADING UITS) FOR ALL COLORS	__ YES __ NO
K	ELECTROSTATIC PROPENSITY TEST (AATC-134)	LESS THAN OR EQUAL TO 3.0 KV	__ YES __ NO
L	CRI GREEN LABEL PLUS CERTIFIED	YES	__ YES __ NO
M	METHANAMINE PILE TEST (DOC-FF-1-70 & ASTM D-2859):	PASSES	__ YES __ NO
N	FLOOR RADIANT PANEL TEST (ASTM-E-648)	CLASS 1 (DIRECT GLUE)	__ YES __ NO
O	FLAMMABILITY TEST (N.B.S SMOKE CHAMBER NFPA 258 & ASTM-E-662):	LESS THAN 450 (FLAMMING MODE)	__ YES __ NO
P	OZONE & GAS TEST (AATCC 129 RATING 3 OR BETTER PER COLOR AATCC TRANSFERENCE SCALE	PASSES	__ YES __ NO
Q	INDOOR AIR QUALITY: CERTIFIED CRI GREEN LABEL PLUS:	YES	__ YES __ NO

SPECIFICATION NO. 1			
R	SMOKE DENSITY TEST (ASTM E-662)	LESS THAN 450 CORRECTED OPTICAL DENSITY (FLAMING MODEL)	___ YES ___ NO
S	INSTALLATION ADHESIVES AND SEAM SEALERS	COMPLIANCE WITH CRI GREEN LABEL PLUS INDOOR AIR QUALITY ADHESIVE TESTING PROGRAM	___ YES ___ NO
T	DELAMINATION TEST (ASTM D3936):	MINIMUM 2.5# PER INCH DELAMINATION RESTISTANCE	___ YES ___ NO
U	NON-PRORATED WARRANTY PERIOD:	MINIMUM 20 YEARS	___ YES ___ NO
V	WARRANTY COVERS: DELAMINATION WET OR DRY:	YES	___ YES ___ NO
W	WARRANTY COVERS: EDGE RAVEL WET OR DRY	YES	___ YES ___ NO
X	WARRANTY COVERS: LOSS OF NO MORE THAN 20LB AVG TUFT BIND TEST, WET OR DRY	YES	___ YES ___ NO
Y	WARRANTY COVERS: WEAR NO MORE THAN 10% FACE YARN LOSS	YES	___ YES ___ NO
Z	WARRANTY COVERS: ADHESIVE FAILURE	YES	___ YES ___ NO
AA	WARRANTY COVERS: BACKING	YES	___ YES ___ NO
BB	WARRANTY COVERS: ANTI-STATIC 3.0KV OR LESS	YES	___ YES ___ NO
CC	ADHESIVE: MEETS OSHA REGULATION 29 CFR 1910.1200	YES	___ YES ___ NO
DD	Texture Appearance Retention Rating (TARR)	GREATER THAN OR EQUAL TO A 3.5 TARR RATING	___ YES ___ NO
EE	STAIN RESISTANCE RATING	MINIMUM RATING OF 8 USING AATCC RED 40 STAIN SCALE	___ YES ___ NO

SPECIFICATION NO. 2			
MEDIUM PERFORMANCE/TRAFFIC CARPET			
A.	CARPET CONSTRUCTION/ SURFACE TEXTURE	TUFTED/ LOOP PILE	___ YES ___ NO
B	CARPET SIZE:	6FT OR 12FT WIDE	___ YES ___ NO
C	YARN WEIGHT (PER SQ. YD.):	GREATER THAN OR EQUAL TO 20oz	___ YES ___ NO
D	FACE YARN:	TYPE 6, 6 and/or Type 6	___ YES ___ NO
E	DYE SYSTEM:	YARN OR SOLUTION DYED	___ YES ___ NO
F	PRIMARY BACKING MATERIAL:	WOVEN SYNTHETIC. JUKE/CANVAS BACK WILL NOT BE ACCEPTED	___ YES ___ NO
G	PRIMARY/SECONDARY BACKING:	IMPERMEABLE MOISTURE BARRIER	___ YES ___ NO
H	TUFT BIND TEST (ASTM D-1335):	LOOP PILE – 3.0 LBS. MINIMUM AVERAGE VALUE	___ YES ___ NO
I	CROCKING TEST (AATCC 165)	COLOR TRANSFER CLASS 4 MINIMUM, WET AND DRY, WHEN TESTED AS SPECIFIED	___ YES ___ NO
J	COLORFASTNESS TO LIGHT TEST (AATCC 16, OPT 3):	COLOR CHANGE BETWEEN THE EXPOSED AND UNEXPOSED CARPET AREAS EQUIVALENT TO A MINIMUM OF GRADE 4 ON THE GRAY SCALE FOR COLOR CHANGE AFTER AN EXPOSURE OF 40 AFU (AATCC FADING UITS) FOR ALL COLORS	___ YES ___ NO
K	ELECTROSTATIC PROPENSITY TEST (AATC-134)	LESS THAN OR EQUAL TO 3.0 KV	___ YES ___ NO
L	CRI GREEN LABEL PLUS CERTIFIED	YES	___ YES ___ NO
M	METHANAMINE PILE TEST (DOC-FF-1-70 & ASTM D-2859):	PASSES	___ YES ___ NO
N	FLOOR RADIANT PANEL TEST (ASTM-E-648)	CLASS 1 (DIRECT GLUE)	___ YES ___ NO

SPECIFICATION NO. 2			
O	FLAMMABILITY (N.B.S SMOKE CHAMBER NFPA 258 & ASTM-E-662):	LESS THAN 450 (FLAMMING MODE)	___ YES ___ NO
P	OZONE & GAS (AATCC 129 RATING 3 OR BETTER PER COLOR AATCC TRANSFERENCE SCALE	PASSES	___ YES ___ NO
Q	INDOOR AIR QUALITY: CERTIFIED CRI GREEN LABEL PLUS:	YES	___ YES ___ NO
R	SMOKE DENSITY TEST (ASTM E-662)	LESS THAN 450 CORRECTED OPTICAL DENSITY (FLAMING MODEL)	___ YES ___ NO
S	INSTALLATION ADHESIVES AND SEAM SEALERS	COMPLIANCE WITH CRI GREEN LABEL PLUS INDOOR AIR QUALITY ADHESIVE TESTING PROGRAM	___ YES ___ NO
T	DELAMINATION TEST (ASTM D3936):	MINIMUM 2.5# PER INCH DELAMINATION RESTISTANCE	___ YES ___ NO
U	NON-PRORATED WARRANTY PERIOD:	MINIMUM 15 YEARS	___ YES ___ NO
V	WARRANTY COVERS: DELAMINATION WET OR DRY:	YES	___ YES ___ NO
W	WARRANTY COVERS: EDGE RAVEL WET OR DRY	YES	___ YES ___ NO
X	WARRANTY COVERS: LOSS OF NO MORE THAN 20LB AVG TUFT BIND TEST, WET OR DRY	YES	___ YES ___ NO
Y	WARRANTY COVERS: WEAR NO MORE THAN 10% FACE YARN LOSS	YES	___ YES ___ NO
Z	WARRANTY COVERS: ADHESIVE FAILURE	YES	___ YES ___ NO
AA	WARRANTY COVERS: BACKING	YES	___ YES ___ NO
BB	WARRANTY COVERS: ANTI-STATIC 3.0KV OR LESS	YES	___ YES ___ NO
CC	ADHESIVE: MEETS OSHA REGULATION 29 CFR 1910.1200	YES	___ YES ___ NO
DD	Texture Appearance Retention Rating (TARR)	GREATER THAN OR EQUAL TO A 3.0 TARR RATING	___ YES ___ NO
EE	STAIN RESISTANCE RATING	MINIMUM RATING OF 6 USING AATCC RED 40 STAIN SCALE	___ YES ___ NO

SPECIFICATION NO. 3			
HIGH PERFORMANCE/TRAFFIC CARPET TILE			
A	CARPET CONSTRUCTION/ SURFACE TEXTURE	TUFTED/ LOOP PILE	___ YES ___ NO
B	CARPET SIZE:	18" X 18", 24" X 24", & 36" X 36"	___ YES ___ NO
C	YARN WEIGHT (PER SQ. YD.):	GREATER THAN OR EQUAL TO 18oz	___ YES ___ NO
D	FACE YARN:	TYPE 6, 6 and/or Type 6	___ YES ___ NO
E	DYE SYSTEM:	YARN OR SOLUTION DYED	___ YES ___ NO
F	PRIMARY BACKING MATERIAL:	WOVEN SYNTHETIC. JUKE/CANVAS BACK WILL NOT BE ACCEPTED	___ YES ___ NO
G	PRIMARY/SECONDARY BACKING:	IMPERMEABLE MOISTURE BARRIER	___ YES ___ NO
H	MODULAR TILE DIMENSIONAL STABILITY (ISO 2551):	+/-0.15 % MAXIMUM	___ YES ___ NO
I	TUFT BIND TEST (ASTM D-1335) MODULAR	LOOP PILE: 8.0 LBS MINIMUM AVERAGE VALUE	___ YES ___ NO
J	CROCKING TEST (AATCC 165)	COLOR TRANSFER CLASS 4 MINIMUM, WET AND DRY, WHEN TESTED AS SPECIFIED	___ YES ___ NO

SPECIFICATION NO. 3			
K	COLORFASTNESS TO LIGHT TEST (AATCC 16, OPT 3):	COLOR CHANGE BETWEEN THE EXPOSED AND UNEXPOSED CARPET AREAS EQUIVALENT TO A MINIMUM OF GRADE 4 ON THE GRAY SCALE FOR COLOR CHANGE AFTER AN EXPOSURE OF 40 AFU (AATCC FADING UITS) FOR ALL COLORS	___ YES ___ NO
L	ELECTROSTATIC PROPENSITY TEST (AATC-134)	LESS THAN OR EQUAL TO 3.0 KV	___ YES ___ NO
M	CRI GREEN LABEL PLUS CERTIFIED	YES	___ YES ___ NO
N	METHANAMINE PILE TEST (DOC-FF-1-70 & ASTM D-2859):	PASSES	___ YES ___ NO
O	FLOOR RADIANT PANEL TEST (ASTM-E-648)	CLASS 1 (DIRECT GLUE)	___ YES ___ NO
P	FLAMMABILITY (N.B.S SMOKE CHAMBER NFPA 258 & ASTM-E-662):	LESS THAN 450 (FLAMMING MODE)	___ YES ___ NO
Q	OZONE & GAS (AATCC 129 RATING 3 OR BETTER PER COLOR AATCC TRANSFERENCE SCALE	PASSES	___ YES ___ NO
R	INDOOR AIR QUALITY: CERTIFIED CRI GREEN LABEL PLUS:	YES	___ YES ___ NO
S	SMOKE DENSITY TEST (ASTM E-662)	LESS THAN 450 CORRECTED OPTICAL DENSITY (FLAMING MODEL)	___ YES ___ NO
T	INSTALLATION ADHESIVES AND SEAM SEALERS	COMPLIANCE WITH CRI GREEN LABEL PLUS INDOOR AIR QUALITY ADHESIVE TESTING PROGRAM	___ YES ___ NO
U	DELAMINATION TEST (ASTM D3936):	MINIMUM 2.5# PER INCH DELAMINATION RESISTANCE	___ YES ___ NO
V	DELAMINATION RESISTANCE OF SECOND BACKING (ASTM D3936)	MINIMUM 2.5 LBS. PER INCH DELAMINATION RESISTANCE	___ YES ___ NO
W	NON-PRORATED WARRANTY PERIOD:	MINIMUM 20 YEARS	___ YES ___ NO
X	WARRANTY COVERS: DELAMINATION WET OR DRY:	YES	___ YES ___ NO
Y	WARRANTY COVERS: EDGE RAVEL WET OR DRY	YES	___ YES ___ NO
Z	WARRANTY COVERS: LOSS OF NO MORE THAN 20LB AVG TUFT BIND TEST, WET OR DRY	YES	___ YES ___ NO
AA	WARRANTY COVERS: WEAR NO MORE THAN 10% FACE YARN LOSS	YES	___ YES ___ NO
BB	WARRANTY COVERS: ADHESIVE FAILURE	YES	___ YES ___ NO
CC	WARRANTY COVERS: BACKING	YES	___ YES ___ NO
DD	WARRANTY COVERS: ANTI-STATIC 3.0KV OR LESS	YES	___ YES ___ NO
EE	ADHESIVE: MEETS OSHA REGULATION 29 CFR 1910.1200	YES	___ YES ___ NO
FF	Texture Appearance Retention Rating (TARR)	GREATER THAN OR EQUAL TO A 3.5 TARR RATING	___ YES ___ NO
GG	STAIN RESISTANCE RATING	MINIMUM RATING OF 8 USING AATCC RED 40 STAIN SCALE	___ YES ___ NO

SPECIFICATION NO. 4			
MEDIUM PERFORMANCE/TRAFFIC CARPET TILE			
A.	CARPET CONSTRUCTION/ SURFACE TEXTURE	TUFTED/ LOOP PILE	___ YES ___ NO
B	CARPET SIZE:	18" X 18", 24" X 24", & 36" X 36"	___ YES ___ NO
C	YARN WEIGHT (PER SQ. YD.):	GREATER THAN OR EQUAL TO 15oz	___ YES ___ NO

SPECIFICATION NO. 4			
D	FACE YARN:	TYPE 6, 6 and/or Type 6	___ YES ___ NO
E	DYE SYSTEM:	YARN OR SOLUTION DYED	___ YES ___ NO
F	PRIMARY BACKING MATERIAL:	WOVEN SYNTHETIC. JUKE/CANVAS BACK WILL NOT BE ACCEPTED	___ YES ___ NO
G	PRIMARY/SECONDARY BACKING:	IMPERMEABLE MOISTURE BARRIER	___ YES ___ NO
H	MODULAR TILE DIMENSIONAL STABILITY (ISO 2551):	+/-0.15 % MAXIMUM	___ YES ___ NO
I	TUFT BIND TEST (ASTM D-1335) MODULAR	LOOP PILE: 8.0 LBS MINIMUM AVERAGE VALUE	___ YES ___ NO
J	CROCKING TEST (AATCC 165)	COLOR TRANSFER CLASS 4 MINIMUM, WET AND DRY, WHEN TESTED AS SPECIFIED	___ YES ___ NO
K	COLORFASTNESS TO LIGHT TEST (AATCC 16, OPT 3):	COLOR CHANGE BETWEEN THE EXPOSED AND UNEXPOSED CARPET AREAS EQUIVALENT TO A MINIMUM OF GRADE 4 ON THE GRAY SCALE FOR COLOR CHANGE AFTER AN EXPOSURE OF 40 AFU (AATCC FADING UITS) FOR ALL COLORS	___ YES ___ NO
L	ELECTROSTATIC PROPENSITY TEST (AATC-134)	LESS THAN OR EQUAL TO 3.0 KV	___ YES ___ NO
M	CRI GREEN LABEL PLUS CERTIFIED	YES	___ YES ___ NO
N	METHANAMINE PILE TEST (DOC-FF-1-70 & ASTM D-2859):	PASSES	___ YES ___ NO
O	FLOOR RADIANT PANEL TEST (ASTM-E-648)	CLASS 1 (DIRECT GLUE)	___ YES ___ NO
P	FLAMMABILITY (N.B.S SMOKE CHAMBER NFPA 258 & ASTM-E-662):	LESS THAN 450 (FLAMMING MODE)	___ YES ___ NO
Q	OZONE & GAS (AATCC 129 RATING 3 OR BETTER PER COLOR AATCC TRANSFERENCE SCALE	PASSES	___ YES ___ NO
R	INDOOR AIR QUALITY: CERTIFIED CRI GREEN LABEL PLUS:	YES	___ YES ___ NO
S	SMOKE DENSITY TEST (ASTM E-662)	LESS THAN 450 CORRECTED OPTICAL DENSITY (FLAMING MODEL)	___ YES ___ NO
T	INSTALLATION ADHESIVES AND SEAM SEALERS	COMPLIANCE WITH CRI GREEN LABEL PLUS INDOOR AIR QUALITY ADHESIVE TESTING PROGRAM	___ YES ___ NO
U	DELAMINATION TEST (ASTM D3936):	MINIMUM 2.5# PER INCH DELAMINATION RESTISTANCE	___ YES ___ NO
V	DELAMINATION RESISTANCE OF SECOND BACKING (ASTM D3936)	MINIMUM 2.5 LBS. PER INCH DELAMINATION RESTISTANCE	___ YES ___ NO
W	NON-PRORATED WARRANTY PERIOD:	MINIMUM 15 YEARS	___ YES ___ NO
X	WARRANTY COVERS: DELAMINATION WET OR DRY:	YES	___ YES ___ NO
Y	WARRANTY COVERS: EDGE RAVEL WET OR DRY	YES	___ YES ___ NO
Z	WARRANTY COVERS: LOSS OF NO MORE THAN 20LB AVG TUFT BIND TEST, WET OR DRY	YES	___ YES ___ NO
AA	WARRANTY COVERS: WEAR NO MORE THAN 10% FACE YARN LOSS	YES	___ YES ___ NO
BB	WARRANTY COVERS: ADHESIVE FAILURE	YES	___ YES ___ NO
CC	WARRANTY COVERS: BACKING	YES	___ YES ___ NO
DD	WARRANTY COVERS: ANTI-STACTIC 3.0KV OR LESS	YES	___ YES ___ NO
EE	ADHESIVE: MEETS OSHA REGULATION 29 CFR 1910.1200	YES	___ YES ___ NO
FF	Texture Appearance Retention Rating (TARR)	GREATER THAN OR EQUAL TO A 3.0 TARR RATING	___ YES ___ NO
GG	STAIN RESISTANCE RATING	MINIMUM RATING OF 6 USING AATCC RED 40 STAIN SCALE	___ YES ___ NO

Technical Specifications

Bid No. 603228-14

Annual Requirements Maintenance Contract for Carpet and Vinyl Flooring

Revised per Addendum No. 2

<u>SPECIFICATION NO. 5</u>			
COVE BASE			
A.	Type:	1/8" Vulcanized Thermoset Rubber Cove Base, 4" & 6" Toed Base	___ YES ___ NO
B	Colors:	Assorted	___ YES ___ NO

<u>SPECIFICATION NO. 6</u>		
VINYL COMPOSITION TILE (VCT)		
Product Information:	Vinyl Composite Tile is produced in 1/8-inch thickness, 12 " x 12" size and complies with the requirements of Federal Specification SS-T-312B, Type IV Composition 1-Asbestos Free and ASTC Designation F-1066-87 Standard Specification for VCT. These product formulations do NOT contain asbestos.	___ YES ___ NO
Definition:	VCT meets the requirements of an "Article" as set forth in Title 29, CFR 1910.1200 Hazard Communication and any other pertinent local, state, and federal laws, regulations and codes. These products are (i) formed to a specific shape or design during end use, and end use function dependent upon their shape or design during end use, and (iii) do not release any hazardous chemical under normal condition of use.	___ YES ___ NO

<u>SPECIFICATION NO. 7</u>		
SHEET VINYL		
Product Information:	Conform to ASTM F1303, Type II, Grade 1, Class A non-asbestos formulated fibrous backing. Minimum wear layer thickness 0.050 inch; and a minimum overall thickness 0.080 inch; and a minimum 6 feet wide; and Extend color and pattern throughout the thickness of the wear layer.	___ YES ___ NO