



# CLARK COUNTY DEPARTMENT OF BUILDING Field Inspection Guideline



<b>SUBJECT:</b> Appliances Not Required To Be Installed at Final Inspection		<b>FIG-E-009</b>
<b>Effective Date:</b> July 2, 2007	<b>Revised:</b> October 22, 2008	<b>Approved By:</b> KTM
<b>Code Chapter:</b>		<b>Page 1 of 2</b>

### Field Application:

Due to the high degree of theft of appliances occurring during the course of construction of residences and the resultant loss of time and money associated to replace and repair damage caused when the appliances are stolen, this department has initiated a program to proceed with final inspections without the installation of many of the appliances previously required.

The following appliances **shall not** be required to be installed prior to final inspection by this department on townhouses, condominiums, and single-family residences. However, please note the conditions that shall be in place to allow for the future installation of the appliance.

- **Dishwasher.** A water supply and air gap fitting shall be in place. A dedicated 120 V circuit shall be installed to a receptacle in an accessible location.
- **Clothes Washer.** Laundry box with drain and hot and cold water bibs shall be in place. A dedicated 120 V circuit shall be installed to a receptacle within 6 feet.
- **Clothes Dryer – Gas or Electric.** A receptacle shall be installed with 6 feet. The dedicated laundry/dryer circuit shall be a 120 volt circuit for the gas installation. The environmental dryer exhaust shall be full size (4”) completed to termination within the limitations of the adopted Uniform Mechanical Code. Gas dryer installations shall have a full size gas stop in place and the outlet of the gas valve shall be plugged or nipped and capped.
  - **Exception:** When the installation of the environmental exhaust exceeds the code limitations, a drawing showing total length, number of 90 degree elbows and duct size shall be completed by a design professional or mechanical engineer and be present on the jobsite for verification by the inspector:
- **Vented Hood Above Range.** Duct work to include screened back-draft damper shall be in place when required. Minimum distances (UMC Section 916.2) above range shall be maintained. A dedicated 120 V circuit shall be installed to a receptacle in the cabinet space above the range.

<b>SUBJECT:</b>	<b>Appliances Not Required To Be Installed at Final Inspection</b>	<b>FIG-E-009</b>
-----------------	--	------------------

<b>Effective Date:</b>	<b>July 2, 2007</b>	<b>Revised:</b>	<b>October 22, 2008</b>	<b>Approved By:</b>	<b>KTM</b>
------------------------	---------------------	-----------------	-------------------------	---------------------	------------

<b>Code Chapter:</b>		<b>Page 2 of 2</b>
----------------------	--	--------------------

- **Refrigerator.** Ice maker connection shall be in place. A 120 V receptacle shall be installed in the refrigerator space.
- **Water Conditioner Equipment.** Conditioner loop shall be in place. A 120 V circuit shall be installed to a single receptacle within 6 feet.
- **Gas Range and Oven Combination.** Gas piping and full sized gas stop shall be in place. A 120 V receptacle shall be installed in the range space.
- **Gas Oven, single or double.** Gas piping and full sized gas stop shall be in place. A 120 V receptacle shall be installed in the range space.

***Note:** All other fixtures and appliances normally requiring installation and inspections shall be required to be installed prior to final inspection.*

The installation of an electrical oven is required at time of final to ensure correct hardwire electrical connection and sizing of circuit breaker. However, if an "Appliance Responsibility Agreement" (Form 901) is completed, signed and submitted by the electrical contractor of record for the residence, this installation requirement shall be waived.

Click the link for a copy of the [Appliance Responsibility Agreement \(Form 901\)](#).