SOUTHERN NEVADA BUILDING OFFICIALS REGIONAL STANDARDS

B-112 -5-2019 PG. 1 OF

2018 IRC

ESCAPE AND EMERGENCY RESCUE OPENINGS

Clark County

Dept. of Building & Fire Prevention 4701 W Russell Rd Las Vegas, NV 89118 (702) 455-3000

Boulder City

Building Department 401 California Avenue Boulder City, NV 89005 (702) 293-9282

Henderson

Building & Fire Safety Dept. 240 Water Street Henderson, NV 89015 (702) 267-3650

Las Vegas Building & Safety Dept. 333 N. Rancho Drive Las Vegas, NV 89106 (702) 229-6251

BASIC REQUIREMENTS


EGRESS WINDOW

- MINIMUM 20" WIDE BY 24" HIGH NET CLEAR
- NET CLEAR OPENING OF NOT LESS THAN 5 SQUARE FEET
- TOP OF SILL TO BE NOT MORE THAN 44" ABOVE THE FLOOR

36" MIN. <u>Δ</u>. Δ

WINDOW WELL

- MINIMUM 36" X 36"
- MINIMUM 9 SQ.FT. CLEAR FLOOR AREA
- TOP OF WALL A MAXIMUM OF 44" ABOVE THE FLOOR OF THE WELL
- A GUARDRAIL IS NOT REQUIRED UNLESS AN EXIT WAY ADJOINS THE WELL



DEEP WELLS

IF THE TOP OF THE WINDOW WELL WALL IS MORE THAN 44" ABOVE THE FLOOR OF THE WELL, EITHER LADDER OR STAIR EGRESS IS REQUIRED. THE LADDER OR STAIR MAY ENCROACH A MAXIMUM OF 6" INTO THE REQUIRED CLEAR FLOOR SPACE.

LADDER EGRESS

INSIDE WIDTH OF NOT LESS THAN 12"

CROSS SECTION

- RUNGS SPACED NOT MORE THAN 18" ON CENTER VERTICALLY
- MINIMUM 3" TOE SPACE
- PERMANENTLY FIXED
- NON-COMBUSTIBLE
- SHALL EXTEND TO TOP OF WALL

STEPPED EGRESS (WITHIN PURVIEW OF SNBO)

- MAXIMUM RISE=12"
- MINIMUM RUN=9"
- MINIMUM WIDTH=30"
- HANDRAIL REQUIRED IF MORE THAN 3 RISERS
- THE TOP STEP MAY BE 44" MAXIMUM BELOW THE TOP OF THE WALL
- PERMANENTLY FIXED

Mesquite

Building Department 10 East Mesquite Blvd Mesquite, NV 89027 (702) 346-2835

North Las Vegas Building & Fire Safety 2250 Las Vegas Blvd. N N. Las Vegas, NV 89030 (702) 633-1577

Pahrump

Building & Fire Safety Dept. 250 N Hwy 160 Suite #3 Pahrump, NV 89060 (775) 751-3373