



DES

**DEPARTMENT OF ENVIRONMENT
AND SUSTAINABILITY**



air quality



desert conservation
PROGRAM



sustainability

4701 W. Russell Road 2nd Floor

Las Vegas, NV 89118-2231

Phone: (702) 455-5942 • Fax: (702) 383-9994

Marci Henson, Director

For DAQ Use Only

Test Results Submittal Form for a Gasoline Dispensing Facility

**This form must be submitted to Air Quality within 60 calendar days after the test date.*

Section 1: Source Information				
Source ID:		Source Name:		
Address:		City:	Zip:	
Test Date:		Time of Test:		
Phase II Design: Assist Balance Healy Other:				
Section 2: Testing Company Information				
Company Name:		Name of Tester:		
Email Address:		Phone Number:		
Section 3: Testing Results				
Test	Test Procedure	Pass	Fail	N/A
Phase I Vapor Recovery (Balance System Only)	Pressure Decay/Leak test: CARB Procedure TP-201.3 (as revised for UST); or TP201.3A (as revised for AST)			
	Static Torque of Rotatable Phase I Adaptors: CARB Procedure TP-201.1B			
	Leak Rate and Cracking Pressure of Pressure/Vacuum Vent Valves: CARB Procedure TP-201.1E (as revised)			
	Flow rate Test: CC_V RTP_1			
	EVR Requirements (if applicable)			
	Leak rate of Drop Tube/Drain Valve Assembly: CARB Procedure TP-201.1C			
	Leak Rate of Drop Tube Overfill Protection Devices and Spill Container Drain Valves: CARB Procedure TP-201.1D			
	Arid Technologies, AT-150 Permeator Compliance Test Procedure: Executive order VR-201-AC and VR-202-AC Assist Phase II EVR System.			
Phase I/II Vapor Assist System	Pressure Decay/Leak test: CARB Procedure TP-201.3 (as revised for UST); or TP201.3A (as revised for AST)			
	Static Torque of Rotatable Phase I Adaptors: CARB Procedure TP-201.1B			
	Leak Rate and Cracking Pressure of Pressure/Vacuum Vent Valves: CARB Procedure TP-201.1E (as revised)			
	Air to Liquid (A/L) Ratio test: CARB Procedure TP- 201.5 (as revised)			
	Dynamic Back Pressure test: CARB Procedure TP-201.4 (as revised)			
	Hasstech Burner Efficiency G-70-164 AA			
	EVR Requirements (if applicable)			
	Leak rate of Drop Tube/Drain Valve Assembly: CARB Procedure TP-201.1C			
	Leak Rate of Drop Tube Overfill Protection Devices and Spill Container Drain Valves: CARB Procedure TP-201.1D			
	Arid Technologies, AT-150 Permeator Compliance Test Procedure: Executive order VR-201-AC and VR-202-AC Assist Phase II EVR System.			

Section 3: Testing Results continued				
Test	Test Procedure	Pass	Fail	N/A
Phase I/II Vapor Balance System	Pressure Decay/Leak test: CARB Procedure TP-201.3 (as revised for UST); or TP201.3A (as revised for AST)			
	Static Torque of Rotatable Phase I Adaptors: CARB Procedure TP-201.1B			
	Leak Rate and Cracking Pressure of Pressure/Vacuum Vent Valves: CARB Procedure TP-201.1E (as revised)			
	Dynamic Back Pressure test: CARB Procedure TP-201.4 (as revised)			
	Flow rate Test: CC_V RTP_1			
	EVR Requirements (if applicable)			
	Leak rate of Drop Tube/Drain Valve Assembly: CARB Procedure TP-201.1C			
	Leak Rate of Drop Tube Overfill Protection Devices and Spill Container Drain Valves: CARB Procedure TP-201.1D			
	Arid Technologies, AT-150 Permeator Compliance Test Procedure: Executive order VR-201-AC and VR-202-AC Assist Phase II EVR System.			
Phase I/II Healy Vapor Assist System	Pressure Decay/Leak test: CARB Procedure TP-201.3 (as revised for UST); or TP201.3A (as revised for AST)			
	Static Torque of Rotatable Phase I Adaptors: CARB Procedure TP-201.1B			
	Leak Rate and Cracking Pressure of Pressure/Vacuum Vent Valves: CARB Procedure TP-201.1E (as revised)			
	Vapor Return Line Vacuum Integrity Test: from current CARB Executive Order G-70-186 series, exhibit 4, (for Model 400)			
	Fillneck Vapor Pressure Regulation Fueling Test: from current CARB Executive Order G-70-186 series, exhibit 5, (for Model 400)			
	Vapor Return Line Vacuum Integrity Test: from current CARB Executive Order G-70-165 series, exhibit 4, (for Model 600)			
	Air to Liquid (A/L) Ratio test: CARB Procedure TP- 201.5 (as revised) (for Model 600, 800, and 900)			
	Healy 900 CARB Executive Order VR 201-1, Exhibit 7, 9 (if applicable), and 14			
	EVR Requirements (if applicable)			
	Leak rate of Drop Tube/Drain Valve Assembly: CARB Procedure TP-201.1C			
	Leak Rate of Drop Tube Overfill Protection Devices and Spill Container Drain Valves: CARB Procedure TP-201.1D			
	Arid Technologies, AT-150 Permeator Compliance Test Procedure: Executive order VR-201-AC and VR-202-AC Assist Phase II EVR System.			
Section 4: Notes				
Section 5: Raw Testing Data				
Please include veeder-root printout(s) and all raw testing data with this form submittal to Air Quality.				
Section 6: Certification Statement & Signature				
I certify that, based on information and beliefs formed after reasonable inquiry, the statements in this document are true, accurate and complete.				
Responsible Official (RO):		RO Title:		
RO Signature:			Date:	